



ADVANCED PAVER CARE

WET LOOK Paver Sealer

*Plus SAND LOCK for
Interlocking Pavers and Bricks*



LOCKS SAND BETWEEN JOINTS AND SEALS IN ONE STEP!

- High Gloss, Easy to Apply
- Rich "Wet Look"
- Low VOC, Lead Eligible
- Deeper Penetrating
- Multi-year Protection
- Resists Color Fading



Professional Results...GUARANTEED!

1-800-486-1414

www.glaze-n-seal.com





“WET LOOK” PAVER SEALER

Plus SAND LOCK for Interlocking Pavers and Bricks

PRODUCT DESCRIPTION

“Wet Look” Paver Sealer is the ideal one-step, easy to apply, product for sealing interlocking concrete pavers and stabilizing joint sand by locking it into place. This state of the art formula offers exceptional, high gloss “wet look” protection with stain resistance (even against oil and grease), resists color fading, efflorescence, weeds and mildew growth on the surface.

SPECIAL FEATURES

- Resists oil, grease and rust stains
- Locks sand (regular or polymeric) between joints
- Reduces efflorescence and freeze/thaw effects
- Prevents weed growth
- Resists abrasion and tire marks
- High gloss

LIMITATIONS

Apply in temperatures between 45° and 90° F. Air and surface temperature should be above 45° F for 24 hours before and after sealing. Clean up applicators with lacquer thinner or similar solvent immediately after use.

Do not use if hydrostatic pressure is likely due to heavy water runoff, poor drainage or a waterproof membrane under the surface. Use on porous surfaces only. For professional use only.

SURFACE PREPARATION

Prior to application of **Glaze ‘N Seal products**, surface must be thoroughly clean and dry. Remove all dirt, oil, grease, paint, efflorescence and surface sealers. General cleaning may be done using **Glaze ‘N Seal Heavy Duty Cleaner for Concrete and Masonry**. For efflorescence stains, use **Glaze ‘N Seal Efflorescence Remover**. When acid has been used for any reason, surface must be neutralized. Allow at least 48 hours of drying time before sealing (72 hours if power washing has been done or if temperature is cool). New concrete pavers should cure 14 days or more before sealing. Applying sealer to a damp or incompletely cured surface may cause a hazy appearance or loss of adhesion.

After tamping down the joint sand (regular or polymeric) and sweeping the application area clean, be sure the sand is at least 1/8-inch below the surface of the pavers. The sand should be dry to its full depth before sealing for the best results.

Note. Before applying **Glaze ‘N Seal** products to the entire surface, test several small areas to verify the product’s appearance, penetration and protective ability.

APPLICATION PROCEDURE

Use garden-type, solvent resistant sprayer, low pressure airless sprayer, or natural bristle brush and squeegee for application. Apply one coat in liberal, saturating manner so that joints are saturated with **Paver Sealer**. Ensure that all joints are flooded to maximize sealer soaking into the dry sand. Squeegee any excess product to avoid puddling on the surface. Allow additional drying time in moist, cool climates. An optional second coat may be applied after two hours if desired to increase protection and gloss. For added slip resistance, **Glaze ‘N Seal Grip ‘N Seal** slip resistance additive may be added to the second coat of sealer.

COVERAGE

75 to 150 square feet per gallon depending on porosity of surface and method of application. Second coat will go 50% further. Do not puddle or over apply.

WARRANTY

Glaze ‘N Seal Product liability, either expressed or implied, is limited solely to the replacement of this product when proven to be defective and does not include any labor costs or consequential damages. It is the user’s responsibility to determine the safety, toxicity and suitability of this product.

SAFETY INFORMATION

Product contains petroleum distillates. Read product label carefully before use.

KEEP OUT OF REACH OF CHILDREN.

VOC <100g/l.

ADVANCED PAVER CARE PRODUCT LINE

“Wet Look” Paver Sealer is part of **Glaze ‘N Seal’s Advanced Paver Care** line of products to protect, maintain, and restore. This state of the art product line includes sealers, polishes, cleaners and restoration products. All products are effective, safe to use and easy to use.

For additional information, contact your Glaze ‘N Seal dealer or contact Glaze ‘N Seal directly.



Quality Products for Concrete, Tile and Masonry

Glaze ‘N Seal Products, Irvine, CA • www.glaze-n-seal.com